

# Q8 Formula Ultra 0W-30

## Description

Synthetic SAE 0W-30 extended drain passenger car engine oil with demonstrated fuel saving characteristics.

## Application

- Specially formulated for Volvo passenger car gasoline and diesel 5, 6 and 8 cylinder engines.
- Q8 Formula Ultra may be used as engine lubricant when one or more of the following specifications are used to describe the required lubricant quality:

## Specifications

ACEA A5/B5

API SJ/CF

## Benefits

- Lubricant designed for Volvo passenger car gasoline and diesel engines
- Specially developed for Volvo turbocharged engines
- Extended drain interval capability
- Excellent engine protection after cold starting
- Demonstrated fuel consumption reduction in gasoline and diesel engines
- Excellent engine performance at all driving conditions
- Outstanding protection against foam formation, rust and corrosion

Properties	Method	Unit	Typical
Viscosity Grade			SAE 0W-30
Absolute Density, 15 °C	D 4052	kg/m <sup>3</sup>	860
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	9.8
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	54.6
Viscosity Index	D 2270	-	167
Apparent Viscosity, -35 °C	D 5293	mPa.s	5660
Pour Point	D 97	°C	<-51
Flash Point	D 92	°C	206
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>=2.9

*The figures above are not a specification. They are typical figures obtained within production tolerances.*

