



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

#### Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

#### Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

#### Sales and Tech Service Support

Phone: 1-800-733-4755

### **LUBRIPLATE FP-150 & LUBRIPLATE FP-150-L**

\*NSF International H-1 Registered

“These products are certified OU Kosher Pareve”

“These products are Halal certified”

LUBRIPLATE FP-150 and LUBRIPLATE FP-150-L are tacky; waterproof adhesive oils, which will resist heavy water wash down and steam. They are NSF International H-1 Registered oils for use in helical gear boxes, chains, linkages, cams, slides and wherever a drip-less adhesive fluid lubricant is desired.

<b><u>Typical Tests</u></b>	<b><u>FP-150</u></b>	<b><u>FP-150-L</u></b>
Viscosity SUS 100°F	1950	510
cSt 40°C	367	103
Viscosity SUS 210°F	126	67
cSt 100°C	25	12
Viscosity Index	93	108
API Gravity	28.4	30.2
Flash Point	395°F/202°C	410°F/210°C
Fire Point	455°F/235°C	450°F/232°C
Pour Point	0°F/-18°C	-5°F/-21°C

LUBRIPLATE FP-150 and LUBRIPLATE FP-150-L are available in the following:

<b><u>Packaging Available</u></b>	<b><u>FP-150</u></b>	<b><u>FP-150-L</u></b>
4/1 gallon plastic jugs	L0735-057	L0736-057
5 gallon pail	L0735-060	L0736-060
16 gallon drum	L0735-061	L0736-061
55 gallon drum	L0735-062	L0736-062

#### **\*NSF International H-1 Registration No's**

(Meets former USDA 1998 Guidelines)

126123

126124

\*Registered H-1 by NSF International for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.

"LUBRIPLATE FP-150 and LUBRIPLATE FP-150-L contain no components derived from TSE/BSE relevant animal species; therefore, they are compliant with the requirements of the TSE Note for Guidance EMA/410/01 Rev. 3 July 2011".