

# Granville FS-D 5W/40

1 Litre, 5 Litre, 25 Litre & 199 Litre



#### **Product Description**

Granville FS-D 5W/40 is a fully synthetic diesel oil with an extended drain capability of up to 24,000 Km (subject to manufacturers recommendation) allowing for the variable service intervals of many modern diesel engines. This oil is NOT suitable for vehicles that have diesel particulate filters fitted.

### Recommended for use by Granville for the following manufacturer's specifications

ACEA B3/B4 API CF BMW LL-01 MB 229.3

VW 502.00

VW 505.00



- \* Ensures lubricant performance over extended drain intervals
- \* Excellent high & low temperature performance
- \* Outstanding fuel effiency
- \* Effective environmental protection

## **Product Usage**

For engines where this specification lubricant is required.

#### **Directions for Use**

As recommended by the engine manufacturer.

#### **Storage Instructions**

Keep sealed in a cool, dry place.

#### **Shelf Life**

5 years from date of manufacture.

Amber liquid **Appearance** Odour Characteristic

**Specific Gravity** 0.852 @ 15.6°C (typical)

Solubility Insoluble in water

>200°C **Flashpoint** 



Image for illustrative purposes only

Size	Part No	Barcode
1 Litre	0208	5020618002086
5 Litre	0201	5020618002017
25 Litre	0215	5020618002154
199 Litre	0220	5020618002208

Revision: 1 | Date: 16/03/2012





# Granville

FS-D 5W/40 1 Litre, 5 Litre, 25 Litre & 199 Litre

81.6 cSt (typical) Kinematic Viscosity @ 40°C Kinematic Viscosity @ 100°C 13.3 cSt (typical)

#### **Safety Precautions**

Please see our latest EC Safety Data Sheets for details.

#### **Transport Classification**

Please see our latest EC Safety Data Sheets for details.

\* The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.

Revision: 1 | Date: 16/03/2012

Tel: +44 (0) 1709 890099 Fax: +44 (0) 1709 891121 Web: www.granvilleoil.com