



## NESTE GEAR S 75W-90

Fully Synthetic Gear Oil

SAE 75W-90

API GL-4

Neste Gear S 75W-90 is made of a fully synthetic base liquid blended with additives for EP, oxidation and rust resistance. In addition, it has excellent cold resistance, which allows for immediate smooth gear operation even at the most severe below-zero temperatures and efficient lubrication in hot operating conditions.

### TYPICAL CHARACTERISTICS

|                                 |       |
|---------------------------------|-------|
| Densitykg/m <sup>3</sup> 15°C   | 843   |
| Flash Point°C (COC)             | 230   |
| Pour Point°C                    | -63   |
| Viscosity Index                 | 181   |
| ViscositycSt/ 40 °C             | 84    |
| ViscositycSt/ 100 °C            | 14,5  |
| Brookfield Viscosity cP/ -40 °C | 28500 |
| Tunnelling point °C             | -55   |

Neste Gear S 75W-90 is a gear oil recommended for year-round use in Nordic conditions. Its additives have been chosen to give gear wheels and bearings efficient wear resistance and the synchro-mesh mechanism the right friction for easy gear change. Used in transmission systems for which API GL-4 is recommended.

API Class GL-4

ZF (Zahnradfabrik Friedrichshafen) nos.13-118

MIL-L2105

Neste Markkinointi Oy

PL 95, 00095 NESTE OIL

www.neste.fi

Technical service

+358 200 11311

Updated 23.3.2006

Print

Close