

GEARWAY OUTBOARD

Transmission oil for outboard engines

Product description

GEARWAY OUTBOARD is a transmission oil that is intended for lubricating propeller gears.

Application areas

GEARWAY OUTBOARD is recommended for oil-lubricated propeller gears where an oil in viscosity class SAE 90 or an oil according to the US demands for Type B Lubricant must be used. GEARWAY OUTBOARD is also recommended for agricultural, washing and hobby machines.

Characteristics and advantages

Incorporates modern additive technology that effectively counters wear, surface fatigue and corrosion. Kind to several types of gasket and sealing material, minimising the risk of leakage. Delivers good gear function in varying operating conditions and temperatures.

Tests and approvals

Specifications: API GL-4

Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on www.statoillubricants.com or supplied on request.

Typical Data

| Characteristics | Typical value | Unit | Method |
|-------------------------------|---------------|--------------------|-------------|
| Brookfield viscosity at -26°C | 150000 | mPas | ASTM D 2983 |
| Density at 15°C | 888 | kg/m ³ | ISO 12185 |
| Flash point COC | 238 | °C | ISO 2592 |
| Pour Point | -33 | °C | ISO 3016 |
| Viscosity at 40°C | 137 | mm ² /s | ISO 3104 |
| Viscosity at 100°C | 14.25 | mm ² /s | ISO 3104 |
| Viscosity index | 102 | - | ISO 2909 |

Revision date 18-Aug-2014