

## Product Information

# GOLDEN FILM FLUSHING OIL

---

## Description

Golden Film Flushing Oil is a combination of highly refined light mineral oils and detergent/dispersant additives to enhance removal of sludge and lacquers. Golden Film Flushing oil can be used where a system's history is unknown or the service fill lubricant may have been used beyond its oil drain interval. This product can also be used if the service fill lubricant has to be drained because of a contamination problem.

## Application

Golden Film Flushing Oil can be used in petrol and diesel engines, hydraulic systems and compressors.

## Directions For Use

- (1) Run the system until it reaches normal running temperature.
- (2) Drain old oil.
- (3) Fill with Morris Flushing Oil between minimum and maximum fill levels.
- (4) Run the system without load for 5 to 10 minutes.
- (5) Drain flushing oil. Repeat steps 2 to 4 if necessary.
- (6) Refill with recommended service fill lubricant.

## Physical Characteristics

Specific Gravity	0.901
Viscosity cSt @ 40°C	22
Viscosity cSt @ 100°C	3.6
Flash Point (Closed) °C	170



Certificate No. FM 21756  
BS EN ISO9001 2000

Morris Lubricants, Castle Foregate, Shrewsbury, Shropshire SY1 2EL

Telephone (01743) 232200 Fax (01743) 353584



Certificate No. EMS 60044  
BS EN ISO14001 1996