

Product Information

GOLDEN FILM RUNNING-IN OIL

Description

Golden Film Running-In Oil is speciality SAE 30 product that should be used for the running in of new or rebuilt petrol and diesel engines, where it promotes the quick and safe bedding in of mating surfaces. The use of Golden Film Running-In Oil during the running in period helps remove the machining glaze from cylinder bores, assists the formation of important oil retaining surfaces, and therefore prevents the possibility of bore polishing. Careful running in using this product can prevent any problems during this period and can greatly extend engine life. Golden Film Running-In Oil is blended from high quality mineral oils and a carefully balanced additive system.

Performance Levels

MIL-L-2104B

Physical Characteristics

SAE Classification	30
Density at 15°C	0.890
Kinematic Viscosity at 100°C	11.6
Kinematic Viscosity at 40°C	98
Viscosity Index	100
Flash Point (Open) °C	210
Pour Point, °C	-20
T.B.N. mg/KOH/g	4.0

TDS Golden Film Running In Oil – 140310 Issue 2



Certificate No. FM 21756
BS EN ISO9001

Morris Lubricants, Castle Foregate, Shrewsbury, Shropshire, SY1 2EL
Telephone (01743) 232200 Fax (01743) 353584



Certificate No. EMS 60044
BS EN ISO14001