

Product Information

GOLDEN FILM 10W-40 CLASSIC MARINE OIL

Description

Golden Film SAE 10W-40 is a high quality, multigrade engine oil designed for use in canal boats. The additive level has been chosen and optimised to prevent bore glazing or bore polishing, whilst keeping engine components clean and protecting them from wear and corrosion.

Applications

Golden Film SAE10W-40 is ideal for use in all engine types, petrol or diesel, installed in canal boats and similar craft requiring a lubricant with this level of performance. Additionally, the SAE 10W-40 classification makes the lubricant suitable for use in all canal boat engines where a SAE 15W-40 may be specified. The SAE 10W-40 properties will ensure that the lubricant flows more rapidly at low temperatures providing improved component protection.

Specifications

API CC/SF

Physical Characteristics

SAE Viscosity Grade	10W-40
Density at 15°C	0.883
Kinematic Viscosity at 100°C	14.1
Kinematic Viscosity at 40°C	95.0
Viscosity Index	150
Flash Point (closed), °C	190
Pour Point, °C	-30

(TDS Golden Film SAE 10W-40 – 220612 Issue 2)



Morris Lubricants, Castle Foregate,
Shrewsbury, Shropshire, SY1 2EL

Telephone (01743) 232200

Fax (01743) 353584