

Product Information

GOLDEN FILM SAE 20W-50 CLASSIC MOTOR OIL

Description

Golden Film SAE 20W-50 Classic Motor Oil is specialist high quality, low detergent/dispersant multigrade lubricant. This oil is suitable for use in naturally aspirated four stroke petrol and diesel engines.

Applications

Golden Film SAE 20W-50 Classic Motor Oil is recommended for use in veteran, classic and vintage cars, motorcycles, commercial vehicles and tractors, where engine design and tolerances prohibit the use of modern high additive level oils.

Golden Film SAE 20W-50 Classic Motor Oil is a low dispersant oil and allows any solid contaminants to drop harmlessly into the sump. This is an important feature where early methods of oil filtration, such as mesh gauzes or strainers are fitted.

The multigrade properties of Golden Film SAE 20W-50 provide improved cold start circulation whilst maintaining good working oil pressure.

Performance Levels

API SF/CC

MIL-L-2104B

Physical Characteristics

Density at 15°C	0.888
Kinematic Viscosity at 100 °C, cSt.	17.5
Kinematic Viscosity at 40 °C, cSt.	135
Viscosity Index	130
Flash Point (open) °C	235
TBN, mg/KOH/g	6.0
Sulphated Ash, %Wt.	0.81
Pour Point, °C	-30

(TDS Golden Film SAE 20W-50 – 220612 Issue 3)



Certificate No. FM 21756



Certificate No. EMS 60044



Certificate No. OHS 555083

Morris Lubricants, Castle Foregate,
Shrewsbury, Shropshire, SY1 2EL
Telephone (01743) 232200
Fax (01743) 353584