

Product Information

GROUNDFORCE 2HSS

Semi-Synthetic 2-Stroke engine Oil for Premix & Injector Systems

Description

Groundforce 2HSS is a top quality synthetic boosted 2-stroke oil, utilising the latest performance additive technology, for protection and performance. Provides maximum film strength and anti-wear characteristics, for prolonging engine life. Groundforce 2HSS is a low smoke, clean burning lubricant and reduces the need for maintenance on ports and exhausts. Provides all season reliability for modern 2-stroke engines when used in horticultural or plant equipment. This lubricant has been developed to meet the need for a specialised product for horticultural contractors and hired equipment where a certain amount of severe treatment has to be catered for and where adherence to mixtures ratios cannot be guaranteed.

Applications

Groundforce 2HSS has been formulated for use in the engines of all two stroke powered horticultural equipment. This includes mowers, chain saws, chippers, shredders, scarifiers, weed cutters, trimmers and hedge cutters. Can also be used in other air-cooled engines powering abrasive disc cutters, angle grinders and general 2-stroke hire equipment. For premix the mixing process and ratios should be as detailed in the manufacturers handbook. Can also be used via a direct injection system.

Performance Levels

JASO FD API TC + ISO-L-EGD

Approved and endorsed by the British Agricultural & General Machinery Association.

Physical Characteristics

Colour	Red
Density at 15 °C	0.867
Kinematic Viscosity at 100 °C, cSt.	8.5
Kinematic Viscosity at 40 °C, cSt.	54
Viscosity Index	135
Sulphated Ash %Wt.	<0.10
Pour Point, °C	-30
Flash Point, (Closed) °C	100

(TDS Groundforce 2HSS – 170311 Issue 3)



Certificate No. FM 21756



Certificate No. EMS 60044



Certificate No. OHS 555083

Morris Lubricants, Castle Foregate,
Shrewsbury, Shropshire, SY1 2EL

Telephone (01743) 232200

Fax (01743) 353584