

## Product Information

# GROUNDFORCE CROMA 30

## Chain Saw Cutter Bar Oil

---

## Description

Groundforce Croma 30 Cutter Bar Oil is designed to meet all lumber industry, forestry, woodyard and estate management requirements. Provides excellent corrosion protection and improved chain performance in a wide range of climatic conditions.

The specially treated base fluids used in the formulation: -

- Reduce wear on cutter bar chain and sprockets.
- Reduce build up of messy foam.
- Resist tendency to fling from fast moving parts.
- Allow use in sub zero temperatures.
- Provide excellent corrosion protection.

## Applications

Groundforce Croma 30 is recommended for use in all chain lubrication systems and should be used in accordance to manufacturer's recommendations. Where biodegradable oils are required or desirable, CROMA VG should be selected.

Groundforce Croma 30 is approved and endorsed by the British Agricultural & Garden Machinery Association.

## Packaging

Package sizes available 1, 5, 25, 205 litre containers.

## Physical Characteristics

<b>SAE GRADE</b>	<b>30</b>
SG at 15 °C	0.883
Viscosity at 100 °C cSt	13.8
Viscosity at 40 °C cSt	120.0
Flash Point (closed), °C	200
Pour Point, °C	-20
Sulphated Ash	Ashless



Certificate No. FM 21756  
BS EN ISO9001 2000

Morris Lubricants, Castle Foregate, Shrewsbury, Shropshire SY1 2EL  
Telephone (01743) 232200 Fax (01743) 353584



Certificate No. EMS 60044  
BS EN ISO14001 1996