



Product Information

GROUNDFORCE SAE 10W-40

Multigrade Engine Oil

Description

Groundforce SAE 10W-40 is designed to cope with the difficult conditions found in four stroke diesel and petrol engines fitted to horticultural, garden machinery and stationary equipment where multigrade oils are recommended. The oil is blended from solvent refined base stocks and performance additives to control varnish, soot dispersancy, low temperature sludge, oxidation, rust and corrosion. Groundforce SAE 10W-40 is recommended for all year use.

Applications

Groundforce SAE 10W-40 is designed for use in all horticultural 4 stroke engines, both diesel and petrol where an oil of this quality is required.

Performance Levels

API SF/CD/CF

Approved and endorsed by the British Agricultural & Garden Machinery Association.

Packaging

Package sizes available 1, 5 and 25 litre containers.

Physical Characteristics

SAE Viscosity Grade	10W-40
Density at 15°C	0.883
Kinematic Viscosity at 100°C	14.1
Kinematic Viscosity at 40°C	95.0
Viscosity Index	150
Flash Point (closed), °C	190
Pour Point, °C	-30

(TDS Groundforce SAE 10W-40 – 220612 Issue 3)



Morris Lubricants, Castle Foregate,
Shrewsbury, Shropshire, SY1 2EL

Telephone (01743) 232200

Fax (01743) 353584