

Product Information

GROUNDFORCE SAE 30

Premium Engine Oil

Description

Groundforce SAE 30 is a low ash lubricant designed for use in older horticultural equipment powered by petrol and diesel engines where monograde oils are recommended. The oil is blended from solvent refined base stocks and performance additives to control varnish, soot, dispersancy, low temperature sludge, oxidation, rust and corrosion.

Groundforce SAE 30 is particularly suitable where machinery has to be laid up between seasons or for plant that is only used intermittently. It prevents internal deterioration caused by damp atmospheres and the extremes of temperatures.

Applications

For use in older diesel and petrol engines in horticultural equipment where an oil to API SF / CC quality is required. Groundforce SAE 30 is approved and endorsed by the British Agricultural & Garden Machinery Association.

Packaging

Package sizes available 1, 5 and 25 litre containers.

Physical Characteristics

SAE Viscosity Grade	30
Density at 15°C	0.887
Kinematic Viscosity at 100°C, cSt.	11.6
Kinematic Viscosity at 40°C, cSt.	98.0
Viscosity Index	100
Flash Point (Closed) °C	200
Pour Point, °C	-25



Certificate No. FM 21756
BS EN ISO9001 2000

Morris Lubricants, Castle Foregate, Shrewsbury, Shropshire SY1 2EL

Telephone (01743) 232200 Fax (01743) 353584



Certificate No. EMS 60044
BS EN ISO14001 1996