



LEVELS OF QUALITY

The lubricant GT MAX 15W/40 complies with the following international specifications:

- API SJ/CF/CF-4
- ACEA A3/B3
- MB 228.1
- VW 500.00-505.00

DESCRIPTION

Duglas Oil GT MAX 15W/40 is a high-quality multigrade lubricant, produced by using carefully selected bases and additives. Its use provide excellent performances in aspirated and turbocharged petrol and diesel engines of cars and light commercial vehicles. It offers a high detergent and dispersant power, an excellent resistance to corrosion and oxidation and a high antifoam power.

The high viscosity index allows use under any climatic conditions (low and high external temperatures).

It provides the maximum protection for engines and guarantees the right viscosity under any operating conditions (cold starts, long distances, etc.).

It is suitable for cars fitted with a catalytic converter.

It is recommended to always observe the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES

SAE Scale	15W/40
Density at 15°C.Kg./dm3 ASTM D1298	0.870
Viscosity at 100°C.cSt ASTM D445	13.2
Viscosity Index ASTM D2270	135
Flammability V.A.°C ASTM D92	210
Pour Point °C ASTM D97	-24
T.B.N. ASTM D2896	6

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

