



LEVELS OF QUALITY

The lubricant GT PLUS 15W/40 complies with the following international specifications:

- API SL/CF
- ACEA A3/B4
- MB 229.1
- VW 501.01-505.00

DESCRIPTION

Duglas Oil GT PLUS 15W/40 is a top-quality lubricant, produced by using high-quality mineral-based oils and developed for petrol engines, but able to satisfy the requirements also of new design diesel engines.

It offers a high detergent and dispersant power, an excellent resistance to corrosion and oxidation and a high antifoam power.

The high viscosity index allows use under any climatic conditions (low and high external temperatures).

It provides the maximum protection for engines and guarantees the right viscosity under any operating conditions (cold starts, long distances, etc.).

It is suitable for cars fitted with a catalytic converter.

It is recommended to always observe the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES

SAE Scale	15W/40
Density at 15°C.Kg./dm ³ ASTM D1298	0.870
Viscosity at 100°C.cSt ASTM D445	13.0
Viscosity Index ASTM D2270	140
Flammability V.A.°C ASTM D92	210
Pour Point °C ASTM D97	-24
T.B.N. ASTM D2896	8

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

