



LEVELS OF QUALITY

The lubricant GT PLUS 20W/50 complies with the following international specifications:

- API SG SF/CD

DESCRIPTION

Duglas Oil GT PLUS 20W/50 is a multigrade and mineral-based lubricant, designed by using carefully selected bases and new conception additives in cars and light commercial vehicles provided with non-turbocharged petrol and diesel engines.

It has been formulated with additives which reduce the formation of deposits, lacquers and sludges both at low and high temperatures. Furthermore it offers protection against rust, wear and corrosion and reduces the oxidation at high temperatures.

It is recommended to always observe the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES

SAE Scale	20W/50
Density at 15°C.Kg./dm3 ASTM D1298	0.880
Viscosity at 100°C.cSt ASTM D445	16.7
Viscosity Index ASTM D2270	130
Flammability V.A.°C ASTM D92	218
Pour Point °C ASTM D97	-18
T.B.N. ASTM D2896	4,5

*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

