

Q8 Heinichen 46

Applications

Q8 Heinichen 46 is designed for a wide range of hydraulic equipment.

Specifications

- MAN 698
- ISO 6743/4, category HM
- DIN 51524 part 2, category HLPD

Benefits

- Optimum anti-wear performance, based on a zincdiakylidithiophosphate additive
- Long service life due to high thermal and oxidation stability for high temperature applications
- Trouble-free operation due to the unique combination of outstanding foam, air release and filterability characteristics
- Emulsifies entrained water

References

- Q8 Heinichen meets the requirements of most hydraulic component manufacturers

Formulation

- Paraffinic mineral oils
- Anti-wear additive
- Rust inhibitor
- Anti-oxidant
- Rust inhibitor
- Anti-foam agent
- Corrosion inhibitor
- Detergent additive

Typical Inspection Data

	Method	Units	Inspection Data
ISO Viscosity Grade	-	-	46
Absolute Density, 15 °C	D 4052	kg/m ³	874
Kinematic Viscosity, 40 °C	D 445	mm ² /s	46.0
Kinematic Viscosity, 100 °C	D 445	mm ² /s	6.72
Viscosity Index	D 2270	-	98
Flash Point	D 92	°C	222
Pour Point	D 97	°C	-24
Colour	D 1500	-	L1.0
Copper Strip, 3 h, 100 °C	D 130	-	1
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Total Acid Number	D 974	mg KOH/g	0.4
Foam			
5 min blowing, seq. 1/2/3	D 892	ml	5/10/5
10 min settling, seq. 1/2/3		ml	0/0/0

Health and Safety

Reference should be made to the relevant Q8 Material Safety Data Sheet before use.

Mar 12



Kuwait Petroleum International Lubricants (UK) Ltd

Knowsthorpe Gate, Leeds LS9 0NP. UK

For further assistance contact the Technical help line Telephone +44 (0) 113 2365 223, Fax +44 (0) 870 238 4673

For Customer Sales Contact, Tel +44 (0) 113 2365 204, Fax +44 (0) 113 2485 026. www.Q8Oils.co.uk

In line with our policy of continued improvement, Kuwait Petroleum International Lubricants reserve the right to change specification and availability without prior notice



Certificate No. FM 89665

technical data