

TOTAL HI-PERF 2T RACING

Oil for 2-stroke gasoline engines

KEY DATA

- 2-stroke oil
- 100 % synthetic engine oil
- Applications :
 - ✓ lubrication of 2 stroke engines equipped with an independant lubrication system
 - ✓ premixing with gasoline
- INTERNATIONAL STANDARDS
 - ✓ JASO FD Level
 - ✓ API TC Level



Customer benefits

- ✓ Very high-tech lubricant for optimal performances in the most extreme conditions
- ✓ Significant reduction in friction for a sporty drive and long-lasting engine protection
- ✓ Makes a permanent oil film, preventing any risk of seizure or binding.
- ✓ Avoids ring sticking
- ✓ Avoids sparks plug fouling.
- ✓ Burns without leaving any sticky deposits.
- ✓ Avoids carbon deposit in the exhaust system.
- ✓ Very good anticorrosion, antirust and antiwear properties.
- ✓ Prediluted to ensure a stable and homogeneous mixture.
- ✓ Perfectly adapted to and leaded fuels.
- ✓ Environmentally friendly lubricant with reduction of smoke exhaust emissions.

Characteristics*

Test	Unit	Result
Viscosity grade	kg/m ³	880
Kinematic viscosity at 40°C	mm ² /s	75,2
Kinematic viscosity at 100°C	mm ² /s	13,7
Viscosity index	-	143
Pour Point	°C	-39
OC Flash Point	°C	108

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

Recommendations for use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

Health, safety and the environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.