

## High Performance Motor Oil

Conoco® High Performance Motor Oil is a high-quality, conventional automotive engine oil recommended for use in gasoline-fueled passenger cars and light trucks operating under high-temperature conditions, such as towing heavy loads, where the vehicle manufacturer specifies an SAE 20W-50 engine oil. It also may be used in gasoline-fueled competition engines and high-performance street engines where SAE 20W-50 engine oil is preferred. It is not recommended for use in new cars under warranty.

High Performance Motor Oil is formulated to provide excellent wear protection, to minimize the formation of sludge and varnish, and to resist viscosity and thermal breakdown, even in severe service. It also protects against rust and bearing corrosion, and is resistant to foaming.

### ***Applications***

- Gasoline-fueled passenger cars, light trucks and sport utility vehicles operating under high-temperature conditions where an SAE 20W-50 engine oil is specified
- Gasoline-fueled competition engines and high-performance street engines

High Performance Motor Oil is licensed for:

- API Service SN

### ***Features/Benefits***

- Excellent resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Excellent wear protection
- Protects against rust and bearing corrosion
- Good foam resistance
- Formulated for engines equipped with turbochargers or superchargers
- Racetrack-proven performance

**Conventional  
Passenger Car  
Engine Oil**

### **CONTACT INFORMATION**

**Phillips66  
Lubricants.com**

U.S. Customer  
Service:  
**1-800-368-7128**

Technical Hotline:  
**1-877-445-9198**

International  
Customer Service:  
**1-832-765-2500**

E-mail address:  
**conocolubricants@  
p66.com**



## High Performance Motor Oil

### Typical Properties

SAE Grade	20W-50
Specific Gravity @ 60°F	0.884
Density, lbs/gal @ 60°F	7.36
Color, ASTM D1500	3.5
Flash Point (COC), °C (°F)	230 (446)
Pour Point, °C (°F)	-30 (-22)
Viscosity, Kinematic	
cSt @ 40°C	155
cSt @ 100°C	19.6
Viscosity Index	145
Cold Cranking Viscosity, cP @ -15°C	6,600
High-Temp/High-Shear Viscosity, cP @ 150°C	5.0
Sulfated Ash, ASTM D874, wt %	1.05
Total Base Number (TBN), ASTM D2896	8.8
Phosphorus, wt %	0.085
Zinc, wt %	0.093

### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2015 Phillips 66 Company. Conoco and its respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.