



## NESTE HYDRAULI 15, 22 SUPER

Super-class multigrade hydraulic oils for outdoor use

ISO VG 15 and 22

Neste Hydraulil Super is top quality Super-class multigrade hydraulic oil for demanding outdoor use. It has an extremely wide operating temperature range and superb cold properties. Cold properties and high viscosity index enable best performance even in extremely cold conditions. Special additives developed for extreme conditions give effective protection against wear, oxidation and corrosion. Due to its good air release and de-emulsibility properties it can be used even in severe conditions.

TYPICAL CHARACTERISTICS	15 Super	22 Super
Densitykg/m <sup>3</sup> 15°C	838	853
Flash Point°C (COC)	200	192
Pour Point°C	-51	-48
Viscosity Index	179	168
ViscositycSt/ 40 °C	15	22
ViscositycSt/ 100 °C	4	5,1
Viscosity cSt/-20 °C	565	664

Neste Hydraulil 15 and 22 Super have excellent cold properties for winter time use.

Neste Hydraulil Super oils are used, for example in excavators, forestry equipments, earth movers, fork lift trucks, cranes etc. hydraulics.

Neste Hydraulil Super series has also ISO VG 32, 46 and 68 grades.

Neste Hydraulil Super meets following requirements:

15 22

X X ISO 11158 HV

X X DIN 51524 part 3 HVLP

Neste Markkinointi Oy  
PL 95, 00095 NESTE OIL  
www.neste.fi

Technical service  
+358 200 11311  
Updated 27.4.2006

Print

Close