

HYDRAULIC HD 26

Hydraulic oil for mobile hydraulic systems

Product description

HYDRAULIC HD 26 is a HTF-type (Hydraulic Transmission) transmission fluid for hydraulic systems and work machines with enclosed gearboxes.

Application areas

HYDRAULIC HD 26 is recommended for work machines and tractors used in heavy-duty applications, and for power steering gears of wheel-drivers.

Characteristics and advantages

HYDRAULIC HD 26 has a high viscosity index, making the oil suitable for use in a wide temperature range. The product also provides good anti-foam properties and wear-protection, fast water separation and air release and excellent filterability. HYDRAULIC HD 26 is based on a mineral oil which together with the additives provides good oxidation stability and good protection against wear and corrosion.

Tests and approvals

WT-31/99/STATOIL

Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available for professional users and are supplied on request.

Typical Data

Characteristics	Typical value	Unit	Method
4-ball, WL	200	kg	ISO 20623
Density at 15°C	870	kg/m ³	ISO 12185
Flash point COC	200	°C	ISO 2592
Pour Point	-36	°C	ISO 3016
Viscosity at 40°C	31.6	mm ² /s	ISO 3104
Viscosity index	143	-	ISO 2909

Revision date 18-Aug-2014