



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

#### **Sales, Service & Distribution Center**

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

#### **Manufacturing, Sales, Service & Distribution Center**

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

#### **Sales and Tech Service Support**

Phone: 1-800-733-4755

### **LUBRIPLATE HYDRAULIC JACK OIL**

**LUBRIPLATE Hydraulic Jack Oil** is a heavy duty, high pressure, anti-wear, and non-corrosive hydraulic fluid recommended for hydraulic jacks and similar applications.

**LUBRIPLATE Hydraulic Jack Oil** has the following features:

- Fluid zinc for anti-wear properties.
- High natural V.I. for stable viscosities throughout a wider operating temperature.
- High aniline point for controlled seal-swelling characteristics.
- Rust and corrosion resistant properties.
- Chemical and mechanical stabilities.
- Foam suppression properties.
- Good heat transfer properties.
- Thermal oxidation stability.
- Good demulsibility properties.

### **TYPICAL TESTS**

Viscosity	
SUS/cSt @ 100°F/40°C	160/31
SUS/cSt @ 210°F/100°C	46/6
Viscosity Index	136
API Gravity	31.6
Color	L2.0
Pour Point °F/°C	-30/-34
Flash Point °F/°C	415/213
Fire Point °F/°C	440/227

**LUBRIPLATE Hydraulic Jack Oil** is available in the following:

#### **Packaging Available**

Carton, 12/1 Quart Plastic Jugs  
Carton, 4/1 Gallons  
5 Gallon Pail  
16 Gallon Drum  
55 Gallon Drum

#### **Part No.**

L0768-054  
L0768-057  
L0768-060  
L0768-061  
L0768-062