



Sasol Hydraulic & Spindle Oil 10

HYDRAULIC OIL, ANTIWEAR, GRADE 10

Description

Sasol Hydraulic & Spindle Oil 10 is a high quality, rust and oxidation-inhibited oil with good anti-wear properties. It provides steel-on-steel and steel-on-bronze lubricity.

Application

Sasol Hydraulic & Spindle Oil 10 is intended for:

- hydraulic systems
- high-speed spindle bearings
- airline lubricators
- certain electric equipment controllers

Features and Benefits

Sasol Hydraulic & Spindle Oil 10 is characterised by low viscosity and low temperature fluidity and is therefore eminently suitable for use in hydraulic jacks and forklifts operating in cold storage rooms.

Product Specifications

DIN 51524 Part 2

Sperry Vickers I-286-S & M-2950-S

Typical Characteristics

Property	Units	Typical	ASTM	IP
Viscosity			D445	71
@ 100°C	mm ² /s	2,4		
@ 40°C	mm ² /s	9,5		
Viscosity Index		65	D2270	226
Pour Point	°C	-48	D97	15
Flash Point (COC)	°C	150	D92	36
Density @ 20°C	kg/m ³	865	D4052	365



Storage and Handling

Use PVC, nitrile or other oil resistant gloves and protective clothing to prevent skin contact. Where eye contact is a potential hazard, goggles should be worn.

Avoid temperatures above 80°C and strong oxidizing agents.

Ambient temperatures and atmospheric pressures normally encountered within buildings or roofed-over outdoor storage areas are acceptable. Avoid entering areas where mists or vapours have built up as a result of abnormal temperatures or pressures without the proper breathing equipment and protective clothing.

Pack Information

<u>Product Code</u>	<u>Pack Size</u>
	20 L
	210 L
	Bulk