

HYDRAWAY HVXA 15 LT

Hydraulic oil, primarily for outdoor use

Product description

HYDRAWAY HVXA 15 LT is a high-quality hydraulic oil for advanced hydraulics working in extremely cold conditions.

Application areas

HYDRAWAY HVXA 15 LT is recommended for hydraulics that have to work at very low ambient temperatures, such as forklift trucks in cold-storage rooms, cranes of various types, military mobile hydraulics, etc. Recommended for hydraulic systems that work with temperatures ranging from -50°C up to +45°C.

Characteristics and advantages

HYDRAWAY HVXA 15 LT is based on highly refined mineral oils reinforced with additives that provide the oil with good wear protection and have excellent values as regards filterability, water-separating capacity and oxidation stability. A distinguishing feature of the product is its high viscosity index, which makes it possible to start hydraulic systems even in extreme cold. The product delivers disruption-free operation at varying temperatures and allows long change intervals.

Tests and approvals

Specifications: MIL-H-5606 A

Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on www.statoil lubricants.com or supplied on request.

Typical Data

Characteristics	Typical value	Unit	Method
Density at 15°C	872	kg/m ³	ISO 12185
Flash point COC	108	°C	ISO 2592
Pour point	-60	°C	ISO 3016
Viscosity at 40°C	14.3	mm ² /s	ISO 3104
Viscosity at 100°C	5.2	mm ² /s	ISO 3104
Viscosity index	356	-	ISO 2909

Revision date 19-Aug-2014