

# HYDRAWAY WHITE 68

Hydraulic oil based on white oil

## Product description

HYDRAWAY WHITE 68 is based on white oil, which provides an improved work environment compared with conventional hydraulic oils.

## Application areas

HYDRAWAY WHITE 68 is recommended for all industrial and some mobile hydraulic systems with high demands on the work environment. The oil is also suitable for mist lubrication of spinning tools. Recommended within the temperature range -25°C to +70°C.

## Characteristics and advantages

HYDRAWAY WHITE 68 is intended primarily for modern, compact hydraulic systems where components require a hydraulic oil with additives to reduce wear. The oil also contains additives to prevent oxidation and foaming. HYDRAWAY WHITE 68 gives minimal wear on components in hydraulic systems. The product provides an improved work environment compared with conventional hydraulic oils.

## Tests and approvals

## Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available for professional users and are supplied on request.

## Typical Data

Characteristics	Typical value	Unit	Method
Density at 15°C	881	kg/m <sup>3</sup>	ISO 12185
Flash point COC	-	°C	ISO 2592
FZG A/8.3/90	8	FLS	CEC-L-07-A-95
Pour point	-36	°C	ISO 3016
Viscosity at 40°C	68	mm <sup>2</sup> /s	ISO 3104
Viscosity at 100°C	8.2	mm <sup>2</sup> /s	ISO 3104
Viscosity index	86	-	ISO 2909

Revision date 19-Aug-2014