

## Granville Hypalube C2 5W/30

1 Litre, 5 Litre, 25 Litre & 199 Litre



#### **Product Description**

Granville Hypalube C2 5W/30 is a new generation, fully synthetic multi-grade engine oil formulated to meet the performance demands of low emission engines which combine high performance, fuel efficiency and emission control. Manufactured to a Mid SAPS (Sulphated ash, phosphorous and sulphur content) formulation. Recommended for all engine types where the manufacturer specifies a C2 oil. It is imperative that the correct oil is used as costly repairs will be required if the wrong specification of lubricant is used.

### Recommended for use by Granville for the following manufacturer's specifications

ACEA C2 API SM/CF PSA B712290

#### **Product Benefits**

- \* Mid SAPS (Sulphated ash, phosphorous and sulphur content) formulation
- \* Fully Synthetic

#### **Product Usage**

Use where recommended by the engine manufacturer

#### **Directions for Use**

Use as required by the engine manufacturer

#### **Storage Instructions**

Store sealed in a cool dry place out of the reach of children

#### Shelf Life

5 years form date of manufacture

**Appearance** Amber liquid Odour Characteristic

**Specific Gravity** 0.855 @ 15.6°C (typical)

Solubility Insoluble in water Kinematic Viscosity @ 40°C 73.62 cSt (typical)



\* Image for illustrative purposes only

Size	Part No	Barcode
1 Litre	0704	5020618007043
5 Litre	0705	5020618007050
25 Litre	0706	5020618007067
199 Litre	0708	5020618007081

Revision: 2 | Date: 21/08/2015





# Granville Hypalube C2 5W/30

1 Litre, 5 Litre, 25 Litre & 199 Litre

PREMIUM PERFORME

Kinematic Viscosity @ 100°C : 11.81 cSt (typical)

**Safety Precautions** 

Please see our latest EC Safety Data Sheets for details.

**Transport Classification** 

Please see our latest EC Safety Data Sheets for details.

\* The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.

Revision: 2 | Date: 21/08/2015

Tel: +44 (0) 1709 890099 Fax: +44 (0) 1709 891121 Web: www.granvilleoil.com