

# Granville Hypalube Semi Synthetic 10W/40

1 Litre, 5 Litre, 25 Litre & 199 Litre



#### **Product Description**

Granville Hypalube Semi Synthetic 10W/40 is a high performance oil suitable for petrol and diesel engines, including turbo, fuel injection and catalytic converters.

# Recommended for use by Granville for the following manufacturer's specifications

ACEA A3/B3 API SL/CF MB 229.1 VW 502.00 VW 505.00

#### **Product Benefits**

- \* Ensures lubricant performance
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficentency
- \* Effective environmental protection

# **Product Usage**

For engines where this specification lubricant is required.

## **Directions for Use**

As recommended by the engine manufacturer.

# **Storage Instructions**

Keep sealed in a cool, dry place.

#### Shelf Life

5 years from date of manufacture.

**Appearance** Amber liquid Odour Characteristic

**Specific Gravity** 0.878 @ 15.6°C (typical)

Solubility Insoluble in water

>200°C **Flashpoint** 

Kinematic Viscosity @ 40°C 92.41 cSt (typical) Kinematic Viscosity @ 100°C 13.7 cSt (typical)



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	0095	5020618000952
5 Litre	0123	5020618001232
25 Litre	991Y	N/A
199 Litre	991B	N/A

Revision: 2 | Date: 22/09/2015



# Granville Hypalube Semi Synthetic 10W/40

PREMIUM PERFORM

1 Litre, 5 Litre, 25 Litre & 199 Litre

## **Safety Precautions**

Please see our latest EC Safety Data Sheets for details.

# **Transport Classification**

Please see our latest EC Safety Data Sheets for details.

\* The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.

Revision: 2 | Date: 22/09/2015