



IFMA Top Treat

IFMA Top Treat is a special additive used to modify the frictional characteristics of hydraulic fluids and other lubricating oils. It helps to eliminate chatter in hydraulic cylinders when added to antiwear hydraulic fluids.

Applications

IFMA Top Treat is recommended for use with antiwear hydraulic fluids to eliminate chatter in hydraulic cylinders. The recommended mixing ratio is 1.25 to 2.5 ounces of IFMA Top Treat to one gallon of antiwear hydraulic fluid.

Features/Benefits

- Helps prevent cylinder chatter in hydraulic and circulating systems.

**Supplemental
Friction Modifier
For Antiwear
Hydraulic Fluids**

CONTACT INFORMATION

**Phillips66
Lubricants.com**

U.S. Customer
Service:
1-800-368-7128

Technical Hotline:
1-877-445-9198

International
Customer Service:
1-832-765-2500

E-mail address:
**lubricants@
p66.com**



IFMA Top Treat

Typical Properties

ISO Grade	46
Specific Gravity @ 60°F	0.94
Density, lbs/gal @ 60°F	7.83
Color, Visual	Brown
Flash Point (COC), °C (°F)	>204 (>400)

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2015 Phillips 66 Company. Phillips 66, 76, Conoco, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.