

Granville Jack Oil

500ml



Product Description

Granville Jack Oil is a fully inhibited hydraulic oil developed specifically for use in hydraulic trolley and bottle jacks. Jack Oil has been specifically formulated to alleviate slow system response and sponginess.

Recommended for use by Granville for the following manufacturer's specifications

ISO 32
ISO VG22

Product Benefits

* Prevents slow response & sponginess

Product Usage

Developed specifically for use for use in hydraulic trolley and bottle jacks.

Directions for Use

As per the manufacturers recommendations

Storage Instructions

Store sealed in a cool, dry place

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Specific Gravity	:	0.861 @ 15.6°C (typical)
Solubility	:	Insoluble in water
Flashpoint	:	215°C
Kinematic Viscosity @ 40°C	:	29.95 cSt (typical)

Safety Precautions

Please see our latest EC Safety Data Sheets for details.



* Image for illustrative purposes only.

Size	Part No	Barcode
500ml	0177	5020618001775





TECHNICAL

Data

Granville Jack Oil

500ml



Transport Classification

Please see our latest EC Safety Data Sheets for details.

Quality Lubricants

Quality Lubricants

Quality Lubricants

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

Revision: 1 | Date: 26/03/2012



Granville Oil & Chemicals Ltd.

29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND

Tel: +44 (0) 1709 890099 **Fax:** +44 (0) 1709 891121 **Web:** www.granvilleoil.com