



NESTE KOMPRESSORI 68, 100, 150

Aircompressor oils

Neste Kompessoroi oils are made of top-quality solvent-refined paraffinic base oils. They contain efficient additives to improve lubrication and to prevent oxidation and corrosion.

Special features of Neste Kompessoroi oils:

- high viscosity index
- good rust resistance
- excellent oxidation resistance
- no foaming
- high flash point

TYPICAL CHARACTERISTICS	68	100	150
Densitykg/m ³ 15°C	874	882	885
Flash Point°C (COC)	254	268	280
Pour Point°C	-24	-24	-21
Viscosity Index	102	98	96
ViscositycSt/ 40 °C	68	100	150
ViscositycSt/ 100 °C	8,8	11,3	14,7

Neste Kompessoroi oils are recommended for air compressors and vacuum pumps. They allow smooth operation even at high compressed-air temperatures and prevent carbon from forming on pressure valves.

Neste Kompessoroi oils exceed the requirements of the Pneurop oxidation test 2.5. They also meet the requirements of the German DIN 51506 VDL standard for compressor oils and those of Atlas Copco.

Neste Markkinointi Oy
PL 95, 00095 NESTE OIL
www.neste.fi

Technical service
+358 200 11311
Updated 29.1.2002

[Print](#)[Close](#)