



## Aral Kosmol HTX extra

Turbine oil type L-TD

### Applications:

The turbine oil Aral Kosmol HTX extra is a specially developed ageing-resistant L-TD type solvent, refined with with good water and air separation ability.

Aral has successfully submitted this product to the strict requirements of the high-quality standard DIN EN ISO 9001. This certification gives you an additional safety assurance with this products quality and the service that can be expected from Aral.

### Technical Data

Viscosity Index		DIN ISO 2909	101
Viscosity			
40 °C	mm <sup>2</sup> /s	DIN 51562	52,5
100 °C	mm <sup>2</sup> /s	DIN 51562	7,4
Density at 15 °C	g/ml	DIN 51757	0,868
Flash point COC	°C	DIN ISO 2592	225
Pourpoint	°C	DIN ISO 3016	-12
Neutralization number	mg KOH/g	DIN 51558-1	0,08
Oxide ash	Gew. %	DIN EN ISO 6245	<0,01
Water separation ability	s	DIN 51589	90
Air release time at 50 °C	min	DIN 51381	3
Corrosiveness			
on copper	Korr. Grad.	DIN EN ISO 2160	1 - 100 A 3

### Remarks:

<br>

All data is subject to development for the product and the production process.

Version-No.: IS0004