

Product Information

LODEXOL FR-X

SPECIALISED TRANSMISSION FLUID

Description

Lodexol FR-X is a high performance, extreme pressure (EP) gear oil, which has excellent cold start fluidity contributing to the overall fuel savings for the vehicle. It also has exceptional high temperature stability, ensuring maximum gear set protection, even under the most arduous operating conditions (high speed/high load). Lodexol FR-X will also protect against rust and corrosion.

Applications

Designed for use in manual gearboxes fitted in passenger cars manufactured by the PSA group or where a gear oil of this type and description is specified.

Performance Level

Complies with PSA B71 2310 and B71 2330

Physical Characteristics

SAE Grade	75W-80
Density at 15°C	0.880
Viscosity at 100°C, cSt.	7.89
Viscosity at 40°C, cSt.	45.14
Viscosity Index	146
Flash Point (Closed) °C	150
Pour Point, °C	-39

(TDS Lodexol FR-X – 021213 Issue 1)



EMS 60044



FM 21756



OHS 555083

Morris Lubricants, Castle Foregate, Shrewsbury, SY1 2EL
Tel: +44 (0) 1743 232 200 Fax: +44 (0) 1743 353 584
tds@morris-lubricants.co.uk www.morrislubricants.co.uk