



Product Information:

LODEXOL HPS 75W-90

HIGH PERFORMANCE FULLY SYNTHETIC GEAR OIL

Description:

Lodexol HPS 75W-90 is an advanced, fully synthetic gear oil developed for highly stressed transmission units, used in light and heavy duty commercial vehicles.

The product has high load carrying ability and will protect all critical components over a wide range of operating temperatures and workloads.

Rapid circulation from cold will ensure essential component protection at start up and eliminate gear selection problems. Lodexol HPS 75W-90 will also provide effective wear, rust and corrosion protection. The extremely strong synthetic base fluid maintains lubricating film integrity under the toughest shock load conditions demonstrating superior performance over conventional mineral oils.

Applications

Lodexol HPS 75W-90 gear oil is designed and recommended for use in manual gearboxes, semi-automatic gearboxes, transaxles, transfer boxes, differentials and final drives, where a SAE 75W-90 lubricant with one of the performance attributes listed below, is specified.

Performance Level

API GL4 / 5

API MT-1

SAE J2360

Scania STO 1:0 (Gearbox)

MB-Approval 235.8

MAN 341 Type Z2 / Type M-3

Mack GO-J

Arvin Merotor 0-76-N

ZF TE-ML 02B, 05B, 07A, 08, 12B, 16F, 17B, 19C, 21B

Iveco

DAF

Physical Characteristics

Density @ 15.6°C	0.871
Viscosity @ 100°C, cSt.	15.3
Viscosity @ 40°C, cSt.	104.0
Flash Point (Closed) °C	135
Pour Point, °C	-57

Figures based on average product values.

Note: Has shown 'no harm in use' where applications specify a lubricant complying with Volvo Transmission Oil 97312.

Part No.s: HPS025, HPS205

(TDS Lodexol HPS SAE 75W-90 – 070715 Issue 8)

