



Product Information:

LODEXOL MTFE 75W **FUEL EFFICIENT AUTOMOTIVE GEAR OIL**

Description

Lodexol MTFE 75W is a high performance, fully synthetic gear oil formulated and optimised for use in automotive gearboxes requiring a low viscosity SAE 75W.

Lodexol MTFE 75W will provide potential fuel saving performance due to its low viscosity, which minimises friction in the gearbox. The product has superior cold start fluidity, ensuring fast circulation around gear systems and providing additional energy savings. At high operating temperatures, the product will continue to provide an outstanding level of component protection under a variety of operating conditions. Powerful EP chemistry not only protects gear and synchro elements, but ensures that all components, including bearings, are rust and corrosion free.

Applications

Lodexol MTFE 75W can be used in manual gearboxes, automated manual gearboxes (AMTs), semi-automatic gearboxes, transaxles and transfer boxes, where a gear oil of this type and viscosity grade is specified. Manufacturers include: Ford, Jaguar, Land Rover, Mazda, Volvo

Performance Level

Ford WSS M2C-200D2*
API GL4

Physical Characteristics

Density at 15°C	0.842
Viscosity at 100°C, cSt.	6.43
Viscosity at 40°C, cSt.	31.93
Viscosity Index	159
Flash Point (Closed) °C	140
Pour Point, °C	-63
Brookfield at -40°C, mPa.s	8540

Figures based on average production values.

**has demonstrated no harm in use.*

Part No.s: TFE001, TFE005, TFE025, TFE205

(TDS Lodexol MTFE 75W – 170915 Issue 3)

