

## Granville LS 80W/90

1 Litre & 5 Litre



### Product Description

Granville LS 80W/90 is a specially formulated extreme pressure gear oil for optimum performance of limited slip differentials. LS 80W/90 is a blend of high quality base oils, performance EP additives and specially selected friction modifiers to provide a lubricant with exacting requirements for limited slip operations.

**Recommended for use by Granville for the following manufacturer's specifications**  
API GL-5



\* Image for illustrative purposes only.

### Product Benefits

- \* Reduces whining and chattering
- \* Ensures clutch plates slide smoothly
- \* Outstanding extremes of temperature protection

### Product Usage

Suitable for limited slip differentials fitted to cars, vans, trucks, buses and agricultural equipment.

### Directions for Use

As recommended by the vehicle manufacturer.

### Storage Instructions

As recommended by the vehicle manufacturer.

### Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Specific Gravity	:	0.890 @ 15.6°C (typical)
Solubility	:	Insoluble in water
Flashpoint	:	222°C
Kinematic Viscosity @ 40°C	:	198 cSt (typical)
Kinematic Viscosity @ 100°C	:	17.9 cSt (typical)

Size	Part No	Barcode
1 Litre	1636	5020618016366
5 Litre	1715	5020618017158





# TECHNICAL

Data

## Granville LS 80W/90

1 Litre & 5 Litre



### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Quality Lubricants

Quality Lubricants

Quality Lubricants

*\* The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

Revision: 2 | Date: 04/05/2012

