



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150

Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491

Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE MARINE & AUTO GUARD

ONE PRODUCT FOR:

MOISTURE DISPLACEMENT RUST PREVENTIVE COATING

PENETRATING FLUID LUBRICANT

MOISTURE DISPLACEMENT

An excellent "wet start" product, featuring outstanding moisture displacement properties.

RUST PREVENTIVE COATING

Possesses exceptional rust-proofing properties. Thirty-day test in humidity cabinet prove its rust-proofing properties. Light in viscosity, promotes rapid and complete draining. Highly recommended for rust-proofing machine tool parts, steel cast parts, etc.

PENETRATING FLUID

Exceptional penetration properties. Recommended for nuts, bolts, valves, heat risers, cables, linkage, etc.

LUBRICANT

In addition to all the other properties, recommended for permanent and positive lubrication over a long period of time.

TYPICAL TESTS

Viscosity SUS @ 100°F 45
cSt @ 40°C 6
Viscosity SUS @ 210°F 31
cSt @ 100°C 1.5
Flash Point, °F/°C 280/138
Fire Point, °F/°C 305/152
Color 5
Appearance Clear to Hazy

PACKAGING AVAILABLE

Also available in Aerosol Cans

LUBRIPLATE Marine & Auto Guard

Part No.

Carton, 4/1 gallon jugs	L0717-057
5 gallon pail	L0717-060
16 gallon drum	L0717-061
55 gallon drum	L0717-062
Carton, 12/12 oz. Aerosol cans	L0774-063

LUBRIPLATE Marine & Auto Guard One product to satisfy four important considerations.