

technical data sheet

Marine S 30/6

Low Speed Marine Diesel Engine Oils

PRODUCT DESCRIPTION

Marine S 30/6, is marine diesel engine oil which is the combination of new additive technology with high quality base oils for low speed Cross-Head type marine diesel engines.

APPLICATIONS

- It is suitable <u>tofor</u> use in low speed Cross-Head model marine main engines.
- It can be used in <u>s</u>Stern-tube and deck equipment if it is <u>recommended</u>advisable by the <u>manufacturer.manufacturing company.</u>

PERFORMANCES

API CF

CHARACTERISTICS

- Its high thermal and oxidation stability provides extended oil change interval.
- Its dDetergent and dispersant additives controls formation of soot and deposit, thereby,so ensures keeps engine parts remain clean and redueces maintanence costs.
- Its aAntiwear additives provides very good protection against bearing wear protection even under heavy loads.

Phone: +90 216 522 69 00



technical data sheet

TYPICAL PROPERTIES

SAE		30
Density@15°C, g/ml	ASTM D 4052	0,899
Viscosity@ 40°C, mm²/s	ASTM D 445	102
Viscosity@100°C, mm²/s	ASTM D 445	11,5
Viscosity Index	ASTM D 2270	95
Flash Point, °C	ASTM D 92	236
Pour Point, °C	ASTM D 97	-10
TBN, mgKOH/g	ASTM D 2896	6
Ash contentKül Miktarı, % weight	ASTM D 874	

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers spesifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.