Product data sheet



MARWAY DD 40

2-stroke diesel engine oil

Product description

MARWAY DD 40 is a mineral oil-based monograde engine oil.

Application areas

MARWAY DD 40 is designed for use in heavy duty diesel engines where engine manufacturers' requirements are low Sulphated Ash. The oxidation resistance of the oil makes it suitable even at high temperatures. The product is suitable for Detroit Diesel two-stroke diesels.

Characteristics and advantages

Quality base oils combined with special additives ensure a long service life for engines. Also recommended for ignition bulb engines.

Tests and approvals

Specifications: API CF-2 (Detroit 2-T Diesel)

Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on www.statoillubricants.com or supplied on request.

Typical Data

Characteristics	Typical value	Unit	Method
Density at 15°C	892	kg/m³	ISO 12185
Flash point COC	248	°C	ISO 2592
Pour point	-21	°C	ISO 3016
TBN	7.4	mg KOH/g	ASTM D 2896
Viscosity at 40°C	127	mm²/s	ISO 3104
Viscosity at 100°C	13.9	mm²/s	ISO 3104
Viscosity index	105	-	ISO 2909