



Megaflow® AW Hydraulic Oil

Megaflow AW Hydraulic Oil is a high-quality antiwear hydraulic oil developed for use in a wide variety of industrial and mobile hydraulic system applications. It meets the performance requirements of all major hydraulic pump manufacturers, and is recommended for use in all types of high-pressure, high-speed hydraulic pumps.

Megaflow AW Hydraulic Oil is formulated to provide excellent wear protection for hydraulic pumps and motors, and to protect hydraulic system components against rust and corrosion. It has excellent oxidation resistance and thermal stability at high temperatures to minimize deposit formation and provide long service life. It has excellent water-separating properties to minimize the formation of emulsions, and is resistant to excessive foam buildup that can cause poor or sluggish hydraulic system response.

Applications

- Hydraulic systems on industrial, mobile and marine equipment
- Automated machine tools
- Elevators, hoists, presses and floor jacks
- Marine cargo winches and steering systems
- Mobile construction equipment
- Service station lifts
- Air tools and other pneumatic equipment lubricated through air line lubricators
- Chain drives
- Electric motor bearings
- Lightly to moderately loaded enclosed industrial gear drives that do not require a compounded or extreme-pressure (EP) gear oil

Megaflow AW Hydraulic Oil meets the requirements of the following industry and OEM specifications:

- Bosch Rexroth RE 90220, Type HLP
- DIN 51524 Part 2, Antiwear Hydraulic Oils, Type HLP
- Eaton-Vickers I-286-S, M-2950-S, 35VQ25A antiwear performance (brochure 03-401-2010 Rev 1)
- Fives Cincinnati P-68 (ISO VG 32), P-70 (ISO VG 46), P-69 (ISO VG 68) (approved)
- German Steel Industry SEB 181222
- ISO 11158:1997, Family H (Hydraulic Systems), Type HM
- Parker Hannifin (Denison) HF-0, HF-1, HF-2
- U.S. Steel 127

**High-Quality
Antiwear
Hydraulic Oil**

CONTACT INFORMATION

**Phillips66
Lubricants.com**

U.S. Customer
Service:
1-800-368-7128

Technical Hotline:
1-877-445-9198

International
Customer Service:
1-832-765-2500

E-mail address:
**lubricants@
p66.com**



Features/Benefits

- Excellent wear protection for hydraulic pumps and motors
- Excellent oxidation resistance and thermal stability
- Protects against rust and corrosion
- Excellent water-separating properties
- Excellent filterability, even in the presence of a small amount of water
- Good foam resistance

Megaflow® AW Hydraulic Oil

Typical Properties

ISO Grade	22	32	46	68
Specific Gravity @ 60°F	0.855	0.862	0.869	0.874
Density, lbs/gal @ 60°F	7.12	7.18	7.24	7.27
Color, ASTM D1500	0.5	0.5	0.5	0.5
Flash Point (COC), °C (°F)	196 (385)	216 (421)	227 (441)	238 (460)
Pour Point, °C (°F)	-40 (-40)	-37 (-35)	-37 (-35)	-33 (-27)
Viscosity,				
cSt @ 40°C	22.0	31.0	46.0	68.0
cSt @ 100°C	4.3	5.4	6.8	8.7
SUS @ 100°F	115	160	237	353
SUS @ 210°F	40.7	44.4	49.0	55.5
Viscosity Index	101	108	100	102
Acid Number, ASTM D974, mg KOH/g	0.38	0.38	0.38	0.38
Copper Corrosion, ASTM D130	1a	1a	1a	1a
Demulsibility, ASTM D1401, minutes to pass	10	10	10	10
Foam Test, ASTM D892, Seq. I, ml	0/0	0/0	0/0	0/0
FZG Scuffing Test, ASTM D5182,				
Failure Load Stage	—	12	12	12
Oxidation Stability,				
TOST, ASTM D943-04a, hours	>5,000	>5,000	>5,000	>5,000
RPVOT, ASTM D2272, minutes	>270	>270	>270	>270
Rust Test, ASTM D665 A&B	Pass	Pass	Pass	Pass
Zinc, wt %	0.043	0.043	0.043	0.043

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2015 Phillips 66 Company, Phillips 66, 76, Conoco, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.



Megaflow® AW Hydraulic Oil

Typical Properties

ISO Grade	100	150	220	320
Specific Gravity @ 60°F	0.878	0.882	0.881	0.887
Density, lbs/gal @ 60°F	7.31	7.35	7.34	7.38
Color, ASTM D1500	0.5	3.0	4.0	5.0
Flash Point (COC), °C (°F)	252 (486)	274 (525)	274 (525)	282 (540)
Pour Point, °C (°F)	-32 (-26)	-21 (-6)	-21 (-6)	-15 (5)
Viscosity,				
cSt @ 40°C	100	149	220	320
cSt @ 100°C	11.0	14.7	19.2	24.3
SUS @ 100°F	523	782	1,162	1,703
SUS @ 210°F	63.9	78.5	97.7	121
Viscosity Index	94	97	98	97
Acid Number, ASTM D974, mg KOH/g	0.38	0.38	0.38	0.38
Copper Corrosion, ASTM D130	1a	1a	1a	1a
Demulsibility, ASTM D1401, minutes to pass	10	10	10	10
Foam Test, ASTM D892, Seq. I, ml	0/0	0/0	0/0	0/0
FZG Scuffing Test, ASTM D5182,				
Failure Load Stage	12	12	12	12
Oxidation Stability,				
TOST, ASTM D943-04a, hours	>5,000	>4,500	>4,500	>4,500
RPVOT, ASTM D2272, minutes	>270	>250	>250	>250
Rust Test, ASTM D665 A&B	Pass	Pass	Pass	Pass
Zinc, wt %	0.043	0.043	0.043	0.043

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2015 Phillips 66 Company. Phillips 66, 76, Conoco, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.