



MERETA 220

Fully synthetic industrial gear oil

Product description

MERETA 220 is a high performance, fully synthetic industrial gear oil. MERETA 220 is based on polyalphaolefin with effective additives, providing exceptional protection for machine components and extending service life.

Application areas

MERETA 220 has been specially developed and optimised for use as a gear oil and circulation oil, as well as for hydraulic systems with extreme temperatures. The product is recommended for operating temperatures of up to +110°C in continuous operation. Temporary temperature peaks of up to +180 °C may be permitted without forming harmful oxidation products or deposits.

Characteristics and advantages

MERETA 220 provides exceptional protection against micropitting and wear in the event of extreme temperatures and heavy loads, as well as extremely good protection against corrosion. The product lubricates very effectively, even at low temperatures, and delivers optimised oxidation stability, which offers very good protection against degradation at high temperatures. These properties produce benefits in the form of problem-free operation, minimal maintenance, extended oil change intervals and a longer service life for bearings and gears. The oil is fully miscible with mineral oil based products.

Tests and approvals

DIN 51517-3 FZG >12


Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used oil at a recycling station or equivalent. Safety data sheets are available on www.statoillubricants.com or supplied on request.

Typical Data

Characteristics	Typical value	Unit	Method
Density at 15°C	857	kg/m ³	ISO 12185
Flash point COC	250	°C	ISO 2592
FZG A/16,6/90	>12	FLS	DIN 51 354
FZG A/8.3/90	>12	FLS	CEC-L-07-A-95
Pour point	-48	°C	ISO 3016
Viscosity at 40°C	220	mm ² /s	ISO 3104
Viscosity at 100°C	25	mm ² /s	ISO 3104
Viscosity index	146	-	ISO 2909

Revision date 18-Aug-2015



Revision date 18-Aug-2015