

Q8 Moto SBK 5W-40

Description

High performance synthetic engine oil for motorcycles with wet clutch systems requiring JASO MA2, SAE 5W-40

Application

- All types of air cooled and water cooled four stroke motor cycle engines requiring JASO MA2 performance.
- Q8 Moto SBK is recommended for severe everyday use of motor bikes and is suitable for use with lead free gasoline.

ACEA A3

JASO MA2

API SM

Benefits

- High performance JASO MA2 clutch friction performance
- Superior ACEA A3 and API SM engine performance at extreme riding conditions
- Excellent engine protection after cold starting
- Offers high oil film strength and thus limiting engine wear
- Synthetic year round engine lubricant
- Provides sustained high oil pressure
- Prevents formation of black sludge
- Low volatility by use of synthetic base oils provides minimized oil consumption
- Good protection against rust and corrosion
- Reduced environmental impact
- Catalyst compatible lubricant

Properties	Method	Unit	Typical
SAE Viscosity Grade	-	-	5W-40
Absolute Density, 15 °C	D 1298	kg/m ³	851
Kinematic Viscosity, 40 °C	D 445	mm ² /s	82.0
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.0
Viscosity Index	D 2270	-	176
Borderline Pumping Temperature	D 3829	°C	-35
Pour Point	D 97	°C	-39
Flash Point	D 93	°C	220
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>=3.5

The figures above are not a specification. They are typical figures obtained within production tolerances.