

## MOTORSYNTH 300 5W-40

## MOTOR OIL

MOTORSYNTH 300 5W-40 an ultra-premium synthetic engine oil, designed to provide outstanding levels of protection and performance

### Features and Benefits

MOTORSYNTH 300 5W-40 is industry proven so you can trust you will get the performance you want from your vehicle.

MOTORSYNTH 300 5W40 provides:

- Outstanding wear protection
- Outstanding engine cleanliness
- Outstanding high temperature protection
- Outstanding low temperature protection

### Applications

MOTOR SYNTH 300 5W-40 is formulated to give confidence of protection beyond that of conventional or semi-synthetic oils. We particularly recommend MOTORSYNTH 300 5W-40 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- For Gasoline and Diesel engines
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions
- Turbo-Chargers and Direct Injection engines
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

ACEA A3 ,B4	API SM/CF
-------------	-----------

### Typical Properties

	MOTORSYNTH 300 5W-40
Density @15° C kg/l, ASTM D 4052	0.850
Viscosity cSt @ 40° C	82
Viscosity cSt @ 100° C	13.5
Viscosity Index	160
Flash Point, °C, ASTM D 92	210
Pour Point, °C, ASTM D 97	-36
TBN,mg KOH/gr	8.0
Color ASTM	1.5
Sulfated Ash, wt%, ASTM D 874	0.95
CP ,(-20°C) CCS	6400

November 2012

### **Delek Lubricants**

P.O.B 31 Lod 71100 ISRAEL. Tel: 972-8-9270820, Fax: 972-8-8247072  
www.deleklubes.com