

# Q8 Mozart AC

## Description

Crankcase oil

## Application

- For all two stroke crosshead engines
- Can also be used to lubricate:
  - Trunk piston auxiliary engines
  - Reverse/reduction gear boxes
  - Sterntubes

## Recommendations

- Q8 Mozart AC is developed for all types of two stroke crosshead marine engines
- Q8 Mozart AC may be used as system oil, when one or more of the following specifications are used to describe the required lubricant quality:

## Specifications

- API CC/CB

## Benefits

- High level of engine cleanliness
- Good corrosion and rust protection
- Good water separation and alkalinity retention
- Readily cleaned by centrifuge
- Reduces number of lubricants

Properties	Method	Unit	Typical
Viscosity Grade	-	-	SAE 30
Absolute Density, 15 °C	D 4052	g/ml	0.886
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	104.7
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	11.7
Viscosity Index	D 2270	-	99
Flash Point, P-M	D 93	°C	224
Pour Point	D 97	°C	-12
Total Base Number	D 2896	mg KOH/g	6.8
Sulfated Ash	D 874	% mass	0.82
Rust Preventive Test, Proc.B, 24 h	D 665	-	Pass
FZG Test, A/8.3/90	DIN 51354	load stage	9 (pass)

*The figures above are not a specification. They are typical figures obtained within production tolerances.*

