

## MULTIFLEET 15W40

### **DESCRIPTION**

Mixed fleet engine oil SAE 15w40, suitable for virtually all (including recent model) passengers cars , many light and heavy trucks and busses as well as for off -road and stationary equipment. Meets latest API and ACEA engine oils requirements.

### **APPLICATION**

For the lubrication of gasoline and diesel engines requiring an engine oil with one or more of the below mentioned API or ACEA specifications. This oil is particularly suitable for engines with EGR (=exhaust gas recirculation) systems and for most engines equipped with a NOx reduction system (SCR).

### **SPECIFICATIONS**

CATERPILLAR ECF-1	MB 229.1 / 228.3	SAE 15W40	ACEA A3/B3/B4/E3/E5/E7
	CUMMINS CES 20076/20077/20078	VOLVO VDS 2/VDS 3	API CI-4/CH-4/CG-4/CF/SL
	MTU Type 2	Renault RLD	VW 505
	EURO 3/EURO 4	MAN 3275/ALLISON C4	MACK EO-M +/EO-N-+ C4

### **PROPERTIES**

- Improved dispersancy through highly effective additive technology.
- Greater protection against soot EGR induced wear and sludge formation.
- More affective use of TBN to neutralize extra EGR related acid.
- Offers both improved "bore polishing "and "corrosion " protection.
- Pistons and valves/valve trains keep extremely clean.
- Exhaust gas catalyst compatible.

### **TYPICAL ANALYSIS**

	MULTI FLEET 15W40
Density at 15 C	0.89
Viscosity at 40 C/ cSt	120
Viscosity at 100 C/ cSt	15
Viscosity index	130
Viscosity at -20 C / cP	<7000
Flash Point C	210
Pour point C	-20°C
TBN	10.0