



Multigear® MTF 75W-80

High performance heavy duty synthetic manual transmission fluid

Product Data Sheet



Product description

Multigear MTF 75W-80 is a high performance heavy duty synthetic manual transmission fluid formulated for use in heavy duty truck synchronised manual transmission systems.

Multigear MTF 75W-80 is formulated with synthetic base fluids in combination with a specifically tuned additive system and offers a drain capability of up to 300,000 km.

Customer benefits

- Long drain capability of up to 300,000km helps reduce maintenance costs and helps optimise uptime
- High performance, specially tuned friction characteristics contribute smooth shifting performance
- Highly durable friction properties offer protection and performance throughout fluid service life
- Robust shear stability helps maintain lubrication performance and system protection over a long fluid service life
- High viscosity index (VI) offers reliable system protection during high temperature operations
- Low temperature fluidity aids rapid fluid circulation at system start-up helping protect critical and vulnerable components
- Extreme pressure (EP) protection promotes resistance to component scuffing and wear, helping reduce maintenance
- Oxidation stability contributes to the resistance of harmful sludge, lacquer and deposit formation
- Compatible with a wide range of seal materials, helping prevent fluid loss
- Offers resistance to rust and corrosion in ferrous and yellow metal components, helping reduce maintenance, downtime and costs

Product highlights:

- Up to 300,000km drain intervals
- Smooth shifting performance
- High performance protection
- Long fluid service life
- High temperature protection
- Selected specification standards include:
 - API
 - DAF
 - Eaton
 - MAN
 - Volvo
 - ZF

A Chevron company product

All trademarks are property owned by Chevron Intellectual Property LLC.





Applications

- Multigear MTF 75W-80 is designed for long drain in heavy duty synchronised manual truck transmissions, including automated models (such as ZF AS Tronic transmissions). Multigear MTF 75W-80 is suitable for use in transmissions fitted with retarders or intarders
- ZF has recently started using a new type of synchroniser component in some of its truck and bus transmissions. These transmissions are indicated by a "TE-ML 01" entry on the name plate. Multigear MTF 75W-80 may also be used for these applications

Approvals, performance and recommendations

Approvals

• DAF	Gearbox oil for ZF and Eaton gearboxes	Approval pending
• MAN	341 Type Z4	Approval pending
• Volvo	97305-89	Approval pending
• ZF	TE-ML 02L	Approved
• ZF	TE-ML 16K	Approved

Performance

• API	GL-4 ¹
-------	-------------------

Recommendations

• Eaton (Europe)	Semi-synthetic (300,000 km/3 years)
• MAN	341 Type E3

¹ Although this product is suitable for use in applications where a GL-4 fluid is specified, it should be noted that the GL-4 specification does not fully address the requirements of synchronized manual transmissions. This fluid is optimized around the needs of commercial vehicle transmissions, and may not give satisfactory performance in applications such as passenger car transmissions.



Multigear® MTF 75W-80

High performance heavy duty synthetic manual transmission fluid

continued

Typical test data

MULTIGEAR MTF 75W-80		
TEST	TEST METHODS	RESULTS
Viscosity Grade		75W-80
Product Code		30439.2
Viscosity, Kinematic, 100°C, mm²/s	ASTM D445	9.6
Viscosity, Kinematic, 40°C, mm²/s	ASTM D445	57
Viscosity, Brookfield, -40°C, mPa.s	ASTM D2983	134,000
Viscosity Index	ASTM D2270	150
Colour	ASTM D1500	1.5
Density, 15°C, kg/l	ASTM D1298	0.860
Flash Point COC, °C	ASTM D92	231
Pour Point, °C	ASTM D97	-42

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheet's.

Health, safety, storage and environmental Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

For more information, go to www.chevronlubricants.com