



## NESTE MULTIHIDRAULI 22

Special hydraulic oil

API GL-5

Neste Multihidrauli 22 is a hydraulic oil with particularly good cold properties based on a naphthenic base oil. It is made to comply with the requirements of Partek Oy's Raisio Works for Multilift equipment. Neste Multihidrauli 22 contains extremely efficient EP additives, and additives for foaming, corrosion and oxidation stability. Special features of Neste Multihidrauli 22 are:

- excellent cold properties
- no wax to block filters
- extremely efficient wear resistance
- extremely high viscosity index
- multi-purpose oil for vehicle hydraulics

### TYPICAL CHARACTERISTICS

Densitykg/m <sup>3</sup> 15°C	901
Flash Point°C (COC)	160
Pour Point°C	-54
Viscosity Index	189
ViscositycSt/ 40 °C	22
ViscositycSt/ 100 °C	5,3
Viscosity cSt/-25 °C	920

Neste Multihidrauli 22 is made primarily to meet the quality requirements for the Multilift equipment produced by Partek Oy's Raisio Works.

Neste Markkinointi Oy  
PL 95, 00095 NESTE OIL  
www.neste.fi

Technical service  
+358 200 11311  
Updated 2.9.2003

[Print](#)[Close](#)