



NESTE MUOTTI L

Form oil

Neste Muotti L is made of solvent-refined base oils, an aromatic-free solvent, and organic additives. The oil is delivered ready for use and does not have to be mixed with water or other oil products.

Special features of Neste Muotti L:

- good loosening capacity
- prevents the formation of bubbles in concrete
- no problems with later concrete finishing, e.g. painting or wallpapering
- protects mould surface from moisture
- does not irritate the skin and is relatively odourless
- prevents rusting in steel moulds
- easy to apply either by spraying or with a brush

TYPICAL CHARACTERISTICS

Densitykg/m ³ 15°C	822
Flash Point°C (COC)	85
Pour Point°C	-48
Viscosity Index	156
ViscositycSt/ 40 °C	3,4
ViscositycSt/ 100 °C	1,4
Colour	light

Neste Muotti L can be applied best by spraying. Only a thin layer is recommended for moulds, since thick layers do not usually help loosening and may cause problems with later surface treatment.'

Neste Muotti L is recommended to be stored at over +10 °C. If it is stored in colder temperatures it should be mixed before use.

Neste Markkinointi Oy
PL 95, 00095 NESTE OIL
www.neste.fi

Technical service
+358 200 11311
Updated 9.11.2007

[Print](#)[Close](#)