



NESTE MUOTTI M

Form oil

Neste Muotti M is made of solvent-refined base oils, an aromatic-free solvent, and organic additives. The oil is delivered ready for use and does not have to be mixed with water or other oil products.

Special features of Neste Muotti M:

- good loosening capacity
- prevents bubble formation in concrete
- causes no problems in later concrete surface finishing such as painting or wallpapering
- protects mould surface against moisture
- does not irritate the skin and is relatively odourless
- prevents steel mould from rusting
- easy to apply by spraying or brushing

TYPICAL CHARACTERISTICS

Densitykg/m ³ 15°C	832
Flash Point°C (COC)	94
Pour Point°C	-48
Viscosity Index	113
ViscositycSt/ 40 °C	6,3
ViscositycSt/ 100 °C	2
Colour	light

The best way to apply Neste Muotti M is by spraying. Only a thin layer is recommended for moulds, since thick layers do not usually facilitate loosening and may cause problems with later surface finishing.

Neste Muotti M is recommended to be stored at over +10 °C. If it is stored in colder temperatures it should be mixed before use.

Neste Markkinointi Oy
PL 95, 00095 NESTE OIL
www.neste.fi

Technical service
+358 200 11311
Updated 9.11.2007

[Print](#)[Close](#)