



Sasol Neat Cutting Oil 22 & 32

METALWORKING FLUID, MINERAL, GRADE 22 & 32

Description

Sasol Neat Cutting Oil 22 and 32 are high cutting oils manufactured on the basis of carefully selected neutral mineral oils and a high tech combination of synergistic EP additives and other selected additives. These two high quality products are chlorine free and produce nearly no oil fog (mist) and have no bad smelling odour.

Application

These products are suitable for non-ferrous metals.

Features and Benefits

Sasol Neat Cutting Oil 22 and 32 make it easily possible to keep to tolerances, extend the tool life and give top quality metal surface finish.

- Low disposal cost (because they are chlorine free)
- Excellent corrosion protection
- Very little oil mist (oil fog)
- Multi purpose usage

Typical Characteristics

Property	Units	Typical		ASTM	IP
		22	32		
Viscosity @ 40°C	mm ² /s	22	32	D445	71
Density @ 15°C	kg/m ³	865	875	D4052	365

Storage and Handling

Use PVC, nitrile or other oil resistant gloves and protective clothing to prevent skin contact. Where eye contact is a potential hazard, goggles should be worn.

Avoid temperatures above 80°C and strong oxidizing agents.

Ambient temperatures and atmospheric pressures normally encountered within buildings or roofed-over outdoor storage areas are acceptable. Avoid entering areas where mists or vapours have built up as a result of abnormal temperatures or pressures without the proper breathing equipment and protective clothing.

Pack Information

Product Code

Pack Size