



Product Bulletin

GULF NO RUST C

Gulf No Rust C is a solvent-cutback petroleum compound designed for use with both ferrous and non-ferrous metals. It forms a continuous protective coating upon evaporation of the solvent. See reverse side for recommended application temperatures.

FEATURES AND BENEFITS:

Gulf No Rust C has unique water displacing characteristics. Additionally, it forms a thin film of protection, providing superior metal surface protection. It provides a coating that will not crack or peel when exposed to a wide range of ambient temperatures.

APPLICATIONS:

Gulf No Rust C is recommended for steel surfaces in a variety of applications including machinery, tools, automotive components, marine hardware, construction equipment and any metal surface requiring a protective coating for storage. It is applied by dipping, spraying or brushing at normal room temperatures. It is removed by petroleum solvents or conventional degreasing methods. Safety precautions should be observed in handling this product due to the solvent content.

Typical Properties

Product Code	Test Method	335381
Viscosity, cSt @ 40°C	ASTM D-445	2.5
Viscosity, SUS @ 100°F	ASTM D-2161	34
Film Type		Transparent, oily
Color		DARK
Flash Point, COC, °F	ASTM D-92	140°F
Flash Point, PMCC, °F	ASTM D-93	125°F
Water Displacement	MIL-C-16173D	PASS
Salt Spray (5%) Hours to Failure, AVG		55
Humidity Cabinet Test, Hours		
Polished Panels	ASTM D-1748	1440+
Sandblasted Panels		1440+

Summary Application Guide

Use	Indoor/Outdoor
Theoretical Coverage, ¹ ft. / gal.	2,000
Film Thickness, mils	0.2
Application Method	Dip/Spray
Application Temperature, °F	40-90
Normal Protection Term, Months	
Indoor	10-12
Outdoor, sheltered	3-4

AVAILABILITY:

Gulf No Rust C is available throughout Gulf's marketing area. Your Gulf representative can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF (4853) or visit Nu-tierbrands.com.

¹ Multiply by .025 to convert to square meters / liter.